

Secoroc Grind Matic HG

Hand-held grinding machine for button bits

Grind Matic HG	Product No. 87002435	Product code 9542
----------------	-------------------------	----------------------

Accessories included in delivery

Adjustable angle connector
Allen key, 2 mm
Allen key, 3 mm
Allen key, 5 mm
Claw coupling (6,3 mm)
Grease gun
Hose (PVC 03)
Hose (PVC 6; L = 0,1 m)
Hose clamp (7-8,5 mm)
Hose clamp (11-13 mm)
Hose clamp (26-38 mm)
Nipple
Pipe (L = 0,3 m)
Seal kit
Seat
Support ring
Operator's instructions and spare parts list

Optional accessories	Product No.	Product code
Lubricator	87002750	9500-2750
Reconditioning tool for grinding cups	87002810	9500-2810

Grinding capacity	
Button size	7-20 mm ($\frac{9}{32}$ "- $\frac{25}{32}$ ")

Technical data

Air pressure, max.	7 bar (101.5 psi)
Air consumption, unloaded	3000 l/min
Air consumption, loaded (at 6 bar, 86 psi)	2520 l/min
Hose dimension, air	12,5 mm ($\frac{1}{2}$ ")
Hose dimension, water	6,3 mm ($\frac{1}{4}$ ")
Idling speed	17000 r/min
Water flushing pressure, max.	4,5 bar (65.3 psi)
Weight, excluding hoses	2,8 kg (6.2 lb)

Grinding cups
Refer to page 12



Grind Matic HG is a complete manual grinding system comprising a grinding machine, grinding cup and a specially designed chuck. The grinding cups are equipped with a rubber bushing, preventing the transmission of vibrations to the machine. The cups can be cooled with either air or water. QuickSnap, our cleverly designed chuck, allows you to change grinding cups quickly and easily. Add to that silent and almost vibrationless operation, and the Grind Matic HG is one of the most operator-friendly hand-held grinders on the market.



QuickSnap, our ingenious chuck, allows you to change grinding cups quickly and easily.