

PRODUCT SPECIFICATIONS

PL-200


Mains / Rechargeable Portable Low Glare Lighting Tower

Portable
360 degree
Lighting
System



LIGHTER, BRIGHTER, FASTER DEPLOYMENT

Unfolding or folding the PL-200 takes just two steps, in under 10 seconds.



4-level adjustable petal angle,
switches from sphere to
hemisphere lighting coverage.




Secure the lamp at any
height with the buckle.


One keys to
release tripod.



Optional ground pegs are
available to secure the
lighthouse, providing wind
and vibration resistance.



CREATIVE DESIGN HIDDEN IN THE DETAILS




360° Lighting.

Biomimetic petal-inspired design for lightweight spherical/hemispherical lighting product.



USB Output

Dual rainproof USB outputs for charging two devices at once, rain or shine.



Phone Stand

Continue working while charging, the hook here can serve as a phone stand.



Stepless Dimming

Plug the driver into the rainproof port to unlock maximum brightness and stepless dimming.

Ultra-long Endurance

Standard Mode Up To **8+ Hours**
(D24-100)

2 type of battery packs with different capacities have same contact slot.



D24-54

Typical working hours 22 hours on
PL-200 Eco mode.



D24-100


Doubled typical working hours to
45 hours.

Multiple batteries, charging, and AC power solutions.
Stay powered and productive!



Uniform illumination with 360-degree coverage and no dead angles

² Lighting Area 1100 m




AC Powered

Up To **12,000** LM

Battery-powered

Up To **6,000** LM

AC	0-12,000LM Stepless Dimmable	
Battery (4 Mode)	Turbo	6,000LM
	Standard	3,500LM
	Balanced	2,200LM
	Eco	600LM





Construction



Maintenance



Infrastructure



Mining



Railway



Emergency



Camping



Sport

One person operation

Less than 6.5Kg excluding battery.



1.3m



2.5m




Specifications

PL-200

Hight	1.3m~2.5m
Weight	6.5Kg (Fitting only)
Power Supply	D24 series battery pack / AC 100-
Lumens	277V 0 - 12,000Lm
Run Times	>8 hours (Standard mode, D24-100)
IP Grade	IP66
Output(USB)	5V 2A (2 Dock)



Size (mm)



Package

Model	PL-200
Size of Carton	138x27x33cm
Gross Weight of Carton	8.3KG±5%
PC S/Carton	1



TechnoComplex
Group of companies

+7 (495) 5-100-109
info@tcgc.ru
www.tcgc.ru